

Motor data sheet

IEC LV MOTORS

M3AA 132ME 6

Definition	Data	Unit	Remarks
Product code	3GAA133350-***K		
Voltage code	D		
Type/Frame	M3AA 132ME 6		
Design	CENELEC		
Efficiency class	IE3		Acc. to IEC 60034-30-1:2014
Rated output P_N	5.5	kW	
Rated voltage U_N	400	V	± 5 % (IEC 60034-1)
Rated frequency f_N	50	Hz	± 2 % (IEC 60034-1)
Rated speed n_N	973	r/min	
Rated current I_N	12	A	
Starting current I_s/I_N	5.8		
Nominal torque T_N	53.9	Nm	
Locked rotor torque T_l/T_N	2		
Maximum torque T_b/T_N	2.9		
Efficiency - full load 100%	88.0	%	Acc. to IEC 60034-2-1
Efficiency - 75%	88.8	%	
Efficiency - 50%	88.2	%	
Power factor - full load 100%	0.74		
Bearing DE/NDE	6208-2Z/C3 6206-2Z/C3		
Sound pressure level L_{pA} dB	61	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm ²	0.04	kg-m ²	
Weight	63	kg	
Motor losses with VSD supply	Efficiency %	Losses in Watts	Relative losses %
Speed 90% Torque 100%	86.8	753	13.7
Speed 50% Torque 100%	80.5	666	12.1
Speed 90% Torque 50%	86.6	383	7.0
Speed 50% Torque 50%	82.0	302	5.5
Speed 25% Torque 100%	64.8	747	13.6
Speed 50% Torque 25%	75.8	220	4.0
Speed 25% Torque 25%	64.5	189	3.4

All data subject to tolerances in accordance with IEC. Data subject to changes.